

Effortless Threading
With the Power of Air!
Serge Like A Pro With Ease!

MO-1000

2-Needle, 2/3/4-Thread Overlock with
Easy Threader and Differential Feed

Easy Threader



MO-1000

Major Features

Convenient Threading With the Easy Threader

Using the new easy threader feature, easily thread the machine from the threading hole to the looper with the power of a strong whoosh of air sent from the electric motor. This amazing function dramatically alters upper and lower looper threading.



Automatic Needle Threader

Quickly thread the needle! With the automatic needle threader, the needle is threaded in 3 easy steps.





Quiet Operation

The sound reducing design minimizes the operating noise and the unit sews with less vibration.



Adjustable Differential Feed

Even with easily stretched fabrics such as knits and georgette, create beautifully sewn finishes by adjusting the differential feed. Adjustments can even be made while sewing



Beautiful Sharp Curve

The distance between the needle and knife is 9.95mm (conventional model:15.5mm),allowing you to sew beautiful inside curves.



Upper Looper Converter 2-/3-Thread Conversion

Switch to 2-Thread sewing simply by pushing the 2-/3-thread changeover attachment to the left, making this operation even easier.



Wide Throat Area

The height of the throat is 72.4mm. Due to this height, the usability of the work space improved infinitely.



LED Sewing Light

The needle area is brightly illuminated. The long-life, energy-efficient and eco-friendly light will not heat up, even after a long period of use.



Waste Collector

Provided as a standard accessory, the waste collector catches cut-off fabric and is useful for keeping the area tidy.








Other Useful Features

- *Automatic rolled hemming
- *Adjustable presser foot pressure
- *Option to deactivate upper knife
- *Cutting width adjusting dial




*Safety feature preventing operation when the presser foot is upper position or the cover is open.

*Thread trimming blade for easy thread cutting

▲UP

Sewing Pattern		
4-Thread Overlock	3-Thread Overlock	2-Thread Overlock
		
3-Thread Rolled Hem	3-Thread Narrow Overlock	Frill 3-Thread Rolled Hem With Diff. Feed
		
3-Thread Flatlock		
		

▲UP

Optional attachments					
					
Blind Stitch Presser Foot Part No. 40138091	Elasticator Presser Foot Part No. 40138095	Cording Presser Foot Part No. 40138099	Beading Presser Foot Part No. 40138106	Piping Presser Foot Part No. 40138103	Gathering Presser Foot Part No. 40138121

▲UP

Specifications

ITEM		SPECIFICATIONS
Number of Threads		2/3/4 Threads
Needle		Household Machine Size 12 or 14
	Left Needle	5-9mm
Overlocking Width	Right Needle	3-7mm
	Rolled Hem	2mm
Stitch Length		1-4mm (Standard:2.5mm)
Differential Feed		0.7-2.0 Ratio
Presser Foot Lift		5mm (Max : 8mm)
Sewing Speed		Maximum 1,500 spm